


NH-AAA1100AR**Ni-MH Battery****Dimensions****Specifications**

Chemical System:	Nickel Metal Hydride
IEC Name:	HR03M
ANSI/NEDA:	1.2H1(AAA)
Camelion Model:	NH-AAA1100AR
Average Weight:	12.5g
Dimension(Ø x H):	10.0 ^{±0.5} x 44.0 ^{±0.5} mm 0.39 ^{±0.02} x 1.73 ^{±0.02} inch
Terminals:	Flat
Nominal Voltage:	1.2Volts
Internal Resistance:	45m-ohm
Capacity(160mA constantly discharge to 1.0V at 25±2℃)	
Minimum:	950mAh
Typical:	1100mAh
Operating Temperature:	-10℃-50℃
Storage Temperature:	15℃-25℃
Relative Humidity:	60±15%

Usage Guide

Shaver



Toy



Digital Still Camera

Cautions**Storage**

Store the battery in a cool, dry and well-ventilated area.

Handling

- 1) Do not heat or disposed in fire or water. Do not modify or disassemble the battery. Do not short-circuit positive (+) and negative (-) terminals.
Keep away from metal or other conductive materials.
- 2) Keep away from infants. If infant happens to swallow the battery, consult a doctor immediately.
- 3) When the battery is stored or disposed, isolate positive (+) and negative (-) terminals of the battery to avoid those terminals touch each other.
- 4) In case the battery electrolyte happen to come into mouth,gargle well enough and consult a doctor immediately.


NH-AAA1100AR

Ni-MH Battery

Storage for 24months


Measurement temperature: $20 \pm 2^\circ\text{C}$

Storage procedure: storage for 24months,
measure the voltage and then perform capacity test



Charge Characteristics


Measurement temperature: $25 \pm 2^\circ\text{C}$



Discharge Characteristics

Measurement temperature: $25 \pm 2^\circ\text{C}$

Charge: $0.1\text{C} \times 16\text{hrs}$




IEC Cycle Life Curve

Measurement temperature: $25 \pm 2^\circ\text{C}$

Procedure: According to IEC61951-2(2011)


7.5.1.2



Temperature Characteristics

Procedure: Charge 16hrs by 0.1C; Rest for 60mins

Discharge to 1.0V by 0.2C



Notice:

Environmental elements comply with 2006/66/EC and US LAW 104-142 requirements. This data sheet is typical information specific to products manufactured at the time of its publication. For the latest information, contact us at: info@camelionbattery.com.