客户品牌:DDPAI	项目名称:DRC01	产品类别:说明书	产品料号:70401000177	版本类型:V1.6	归档日期:20231013

80 mm

132 mm

RANGER
User Manual

认识 Ridecam 骑行相机

4K 30fps/2K 60fps/1080P 90fps 帧率相机，采用 IPX 防水防尘等级，可应对多种骑行场景下的稳定画面拍摄，机身顶部集触摸屏，便于交互操作，顶部下配四颗，内部搭载高达512G内存卡容量，支持循环覆盖功能可实现多种应行车/骑行车辆行驶数据，产品机身具备 IPX7 级防尘防水，可提配半重配件长不同骑行工具使用。

❶ 操作说明

• 按键操作说明

按键操作	功能状态说明
【长按左键 3 秒】	【关机】状态下:开机 【录像】状态下:结束录像 【拍照】状态下:关闭拍照 【拍照过程】期间:关机
【单按左键 1 秒】	【录像】状态下:录像暂停 【拍照】状态下:开启录像模式
【长按左键 3 秒】	【录像】状态下:结束录像并启动录像保存程序【拍照】状态下:拍照中止录像中止录像保存程序【拍照】期间:立即关闭录像程序【拍照】期间:立即关闭录像程序

• 指示灯状态说明

指示灯状态	功能状态说明
【常亮】	开机状态
【常亮】	录像状态
【常亮】	升级过程
【闪烁】	存储卡/电源过高
【闪烁】	拍照事件/拍照模式
【闪烁】	USB传输模式
【闪烁】	上电模式

• 屏幕触控使用说明

【从左到右滑动】进入相册
【从右向左滑动】进入数据界面
【从上往下滑动】进入设置页面

• 重置键

• 产品电充方式

• 内容导出方式

❷ 规格参数

产品名称	Ridecam
产品型号	DDPAI RANGER
电池容量	1000mAh
产品尺寸	52*46*26mm
重 量	75±5g

❸ 主机包装清单

APP操作指南

请扫描下方二维码或通过苹果/安卓应用市场搜索"行车记录"下载行车App。

DDPAI App
App Store
Android

安全操作指引

❶ 清洁

1. 设备头保护盖上有荧粉时，他荧粉荧光未发或荧荧微头笔，镜头气体，镜头有污渍工具进行清洁，更换镜头保护盖时，确保密封不漏，以免损坏头孔，同要保干，避免镜内的水进入镜头保护盖内应等待脱盖，请切勿繁拆镜头保护盖，以免导致已经导致公差入镜头盖产品，内部有线圈要盖。
2. 设备头上有荧粉时，使用镜头笔，镜头气体，镜头有污渍工具进行清洁。
3. 防雨设备的门头有荧粉时，使用干棉，及时的水或纸杂或气体进行清洁。
4. 快拆底座内注意防止灰尘，及时用密闭盖密闭。

❷ 警告

1. 请勿拆卸产品，如需维修，为确保产生安全影响，请送商服务，C. 不，镜头内发现异设备，可以使用酒精，请勿，200 以外发现不可设备。
2. 设备的相关设置无时间不等在产品的重性设置与功能未设行，请切记行设置前应必要预留时，否则有生活为或时，也是生要性，请使用更新时下净料有关时清理产品上的水分及异物。
3. 机身扩展接口需要有卷或盖可用，必须先确认扩充卡已经内设备卷或盖等等操作，否则特设备工不可或等设置。
4. 禁止拆卸机机的产品器，否则对设备无风险为，请勿产品设置电源设备拆卸。
5. 用产品发生起火，请立即使用水，水雾，沙，灭火器，干粉，二氧化碳灭火器灭火，请勿直接浸泡/放置入注意指导并及灭火方式。
6. 请在温度为 -20℃ 至 45℃ 之间的环境中使用产品。
7. 产品的充电环境温度为 5℃ 至 40℃，为防止产品设置电池的寿命，并机对各了在所温度等待设置等充电，请立在关机状态下充电。
8. 禁止以任何方式拆解产品，否则解决任何解决，请勿产品设置电池的寿命，并机对各了在所温度等待设置等充电，请立在关机状态下充电。
9. 切勿向产品进行加热，请勿将产品放置于接近炉或灶子或明火。
10. 禁止将产品放在高温（比如在阳光直照下）的地方以及将产品置于热天的汽车内，切勿将产品存储在超过 60℃ 的环境下。
11. 切勿将电池组放置在电线长时间环境，以避免电池进入过放状态而造成电芯损坏，相关法规要使用。

❷ 小心

1. 过度降温或空间过大外产或要可能会使 Ranger 损坏，导致工作异常。
2. 请勿将头保护盖密封，请勿可能会的镜头保护盖等等造成密封，请立即拆盖密封不要清洁 Ranger。
3. 镜头保护盖有脏污或，请小心处理避免损伤。
4. 使用 Ranger 的过程中请注意防止坠落，若机身出现摔坠，请检查内外。
5. 请勿使用以硬物刮擦 USB-C 接口，以免孔，相同。
6. 使用 Ranger 置于低于或使用的环境，但是或高温条件可能会或暗电池的使用时间，或者不能等于不能正常工作。
7. 请勿长产品的使用 Ranger。
8. 请勿自行拆解和维修 Ranger。
9. 请勿在温度、湿度性质等中使用 Ranger。不建议在低或大环境，不相差等环境中使用 Ranger。
10. 将 Ranger 固定于有外时，若车速过快，机动车速度行车杂质，或遇到大风和雨的天气时，请等待 Ranger 的固定，以防发生意外。
11. 请勿在天下使用设备。
12. 在恶劣条件行外时，长期（超过 4 个月）在电量设置设备和电池使用寿命。
13. 超过 10 天不使用 Ranger，请将电池充电至电量 40%-60% 电量存放，可延长电池的使用寿命。

保修说明

产品自出厂日期起，产品出现产品性能故障的 3 年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受更优质保服务。

1. 自您收货日起12个月，产品出现产品性能故障的 3 年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受更优质保服务。
2. 自您收货日起12个月，产品出现产品性能故障的 3年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受更优质保服务。
3. 自您收货日起12个月内，产品出现产品性能故障的 3年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受维修服务。

产品自出厂日期起，产品出现产品性能故障的 3 年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受更优质保服务。

❶ 保修期限

1. 自您收货日起12个月，产品出现产品性能故障的 3 年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受更优质保服务。
2. 自您收货日起12个月，产品出现产品性能故障的 3年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受更优质保服务。
3. 自您收货日起12个月内，产品出现产品性能故障的 3年内性能故障的情况，经由灯灯商品服务中心检测确认，可免费享受维修服务。

❷ 非保修条例

1. 未经授权的维修，使用不当（如强度、挤压、浸泡、碰撞造成等人为原因）而造成的人为损坏。
2. 已超过三年有效期。
3. 因不可抗力造成的损坏。
4. 不符合产品性能使用要求所致故障情况。
5. 因人为原因导致本产品无法实现外产生产品性能故障的 3年内性能故障。
6. 产品使用过程中正常的老化、磨损、脱色等。

❸ 产品性能故障表

1. 设备不通电	2. 喇叭异常/无声	3. 无WiFi信号
4. 电源键失灵	5. 摄像机热异常	

三包凭证

❶ 用户信息

姓　名：
电　话：
电子邮件：
邮政编码：
联系地址：

❷ 产品资料

主机机身SN号：

▶ 维修记录

销售日期	故障现象	处理方案	维修人员签字

有害物质状态说明

有毒有害物质及元素	部件名称				
	塑胶壳体	电路板组件	喇叭	电源	电源线
铅 (Pb)	○	×	○	×	○
汞 (Hg)	○	○	○	○	○
镉 (Cd)	○	○	○	○	○
六价铬(Cr)	○	○	○	○	○
多溴联苯 (PBB)	○	○	○	○	○
多溴二苯醚 (PBDE)	○	○	○	○	○

◎ 表示该部件所含有/使用/或包括在它的零件中的含量均在GB/T26572-2011所规定的限量要求以下。

○ 表示该有毒有害物质在该部件的某一均质材料中的含量超出GB/T26572-2011所规定的限量要求。

× 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出GB/T26572-2011所规定的限量要求。

备注:表中标记"×"的部分中的三氧化物质或铅的电子元器件(如高压电容、陶瓷电容、二极管等)中的含量可能>0.1%，请们，数据仅中的还已区别有性能的部分由，因在含量可能>0.1%，这在最终可能的范围内应在要求的服务条件，即在适合于全球使用发展水平的情况可应可能产品的技术和部件，产品所可能解决的技术量的平均水平要求。

联系我们

制 造 商：灯灯智(深圳)技术股份有限公司
客服热线：400-897-3068
服务时间：周一至周日9:00-18:30(国家法定节假日除外)
官网网址：www.ddpai.com
公司地址：广东省深圳市南山区国际创新谷AA单元3F

Meeting Your DRC01

RANGER DRC01 Ridecam, which can generate 4K 30fps/2K 60fps/1080P 90fps high-definition video, with IDS intelligent anti-shake algorithm, enable stable picture and videos in various scenes. The camera is designed with a touchscreen, which is convenient for interactive operation, playback and parameter setting. Equipped with a 512G internal storage and overlay storage, the camera supports riding mode to prevent a variety of bicycle/motorcycle riding data. This camera comes with IP67 dust and water proof, and can be used with various riding accessories.

❶ Operation Instructions

• Button Function

Button	Function
Power Button	• Hold 1s to power on the device • Quick press to return to main interface • Hold 2s to power off the device • Hold 10s to force shutdown
Left Button	• Quick press to take a photo/start video • Hold 1s to start/end recording
Right Button	• Quick press to switch the data interface • Hold 1s to enter/exit the ride mode • After pausing, quick press to continue recording and close the pop-up window • After pausing, hold 1s to end the riding mode

• Indicator Guide

Indicator	System Status
Breathing Green	Power On (Not Recording)
Steady Green	Recording
Flashes Green	Upgrading
Flashes Yellow	Abnormal Storage / High Temperature
Flashes Purple	Taking Pictures / Short Videos
Steady Purple	USB Transfer Mode
Steady Red	Moment of Power On

• Touchscreen Guide

Swipe Right: Enter Album
Swipe Left: Enter Data Interface
Swipe Up: Enter Settings Interface

• Bracket Installation

• Charging



• Type-C and Wireless Transmission



❷ Specifications

Product Name	Ridecam
Product Model	DDPAI RANGER
Battery Capacity	1000mAh
Dimensions	52*46*26mm
Weight	75±5g

❸ Package Contents

APP Instructions

Please scan the QR code below or search for "DDPAI" in Google Play Store (Android) or App Store (iOS) to download the DDPAI App.

DDPAI App
App Store
Android

Safety Instructions

❶ Cleaning

1. When there are foreign objects on the lens protection cover, it is recommended to clean it with clean water or use tools such as lens pens, lens air blowers, and lens wipes. Avoid using hard objects to scrape the lens protection cover or wipe it with cloth. After the device is out of the water, it needs to be dried to avoid fogging caused by the water in the gap entering the lens protection cover. Do not disassemble the lens protection cover frequently, so as to avoid dust entering the lens cover during disassembly and assembly, which will affect the shooting quality.
2. When there are foreign objects on the lens, use lens pen, lens air blower, lens cloth and other tools to clean them.
3. If there are foreign objects in the cover of the data power supply, please clean them with a dry, soft cloth or paper or air blower.
4. Pay attention to dust and sand in the quick-release base, otherwise it will affect assembly stability of the device.

❷ Warnings

1. The device contains strong magnetism. To avoid the effect of magnetization, please keep away from magnetic cards, IC cards, implanted medical devices (such as pacemakers), hard drives, AM chips and other vulnerable devices.
2. The built-in waterproof membrane of the sound pickup hole and the air pressure balance hole of the device is specially designed for waterproofing. Do not remove the printing by yourself or use sharp objects to damage it, otherwise the waterproof function will be lost. It is recommended to use a soft clean cloth to clean the moisture and foreign matter on the device in time.
3. When there is water or dirt on the surface of the extension interface of the device, it must be wiped clean before connecting power supply accessories and other operations. Otherwise it will stop working or cause corrosion.
4. Do not dry the device with a hair dryer, otherwise the microphone membrane and the built-in breathable membrane will rupture and water will enter.
5. If the product catches fire, please immediately use water, spray, sand, fire blanket, powder, carbon dioxide fire extinguisher to extinguish the fire. Please select the fire extinguishing method from above according to the actual situation.
6. Please use the product in an environment where the temperature is between -20℃ and 45℃.
7. The charging environment temperature of the product is 5℃ to 40℃. To optimize the life of the built-in battery, charging will be suspended when the temperature limit is reached in the power-on state, and it is recommended to charge in the power-off state.
8. Do not disassemble the product in any way. If the battery is pierced during disassembly, the electrolyte inside the battery will leak, and even cause fire and explosion. Please keep the product away from fire, crush or throw the product. Do not place heavy objects on the product.
9. Do not heat the product. Do not place the product in microwave or pressure cooker.
10. It is forbidden to place the product near a heat source (stove or heater, etc.) and to place the product in a car on a hot day. Do not store the product at temperatures above 60℃.
11. Do not store the battery for a long time after it has been fully discharged to avoid battery damage caused by over-discharge. Otherwise, the device will no longer function properly.

❸ Notes

1. Falling from a high place or being subjected to excessive external impact may damage the device and cause abnormal operation.
2. Make sure the lens protection glass is clean. Foreign matter may scratch the lens protection glass and cause image quality damage. It is recommended to clean the device with a soft dry cloth.
3. If the lens protection glass is accidentally damaged, please handle it carefully to avoid injury.
4. When using the device, please keep it away from dust and sand. If the sound pickup hole of the device is blocked by foreign matter such as sand and dust, please wash it with water.
5. Do not use sharp objects to poke the USB-C interface, pickup holes, and other holes.
6. Do not place the device in extreme cold or heat. Low or high temperature environments may shorten battery life or cause temporary malfunction.
7. Do not use the device in thunderstorm weather.
8. Do not disassemble and repair the device by yourself.
9. Do not use the device in hot springs, corrosive liquids. It is not recommended to use the device in extreme water environment, or unknown liquid environment.
10. When the device is fixed outside the vehicle, if the speed of the vehicle is too fast, there are impurities on the surface of the vehicle, or in strong winds or rainstorms, the fixing of the device will be affected, resulting in falling.
11. Do not use the device underwater.
12. If the battery is low, please charge it in time. Long-term (more than 4 months) low battery storage will affect the service life of the battery.
13. If the device is not used for more than 10 days, please charge or discharge the battery to 40%-60% for storage, which can prolong the service life of the battery.
14. The use distance of the human body is more than 15mm.

FCC Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference.

2. This device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

FCC ID:2AJFX-RANGER

Contact Us

Manufacturer: DDPAI (Shenzhen) Technology Co., Ltd.
E-mail: feedback@ddpai.com
Website: www.ddpai.com
Address: 2BF, Building 6A, International Innovation Valley, Nanshan District, Shenzhen City, Guangdong Province

洋红:间距标注
红色:切割刀模
黄色:压线刀模
绿色:字体标注
蓝色:尺寸标注

DDPAI	设计人员:徐小云	包装类型:说明书	材质:80g圣经纸	工艺:骑马钉	颜色:材料浅黄色
	归档人员:徐小云	项目经理:黄念念	比例尺寸:1:1	尺寸:80*132mm	公差:±0.5mm